

Panel & Pleated Filters

6000

Product Overview

- Designed for heavy loading conditions
- More dirt-catching media surface area
- Viscosine® adhesive
- Progressive density media construction
- High compression strength
- Environmental friendly



PANEL & PLEATED
FILTERS

Specification

| | |
|------------------------------|-----------------------------------|
| EN779 | G3 |
| ASHRAE 52.2 | MERV 5 |
| Filter Depth (mm) | 22, 44 |
| Media Type | Fibreglass |
| Frame Material | Moisture Resistant Beverage Board |
| Special Size Available | Yes |
| Antimicrobial Available | No |
| Recommended Final Resistance | 250 Pa |
| Max Operating Temperature | 65°C |

Product Information

| Part Number | Nominal Size Inches (W x H x D) | Actual Size mm (W x H x D) | Rated Airflow (CMH) | Rated Initial Resistance (Pa) |
|--------------|---------------------------------|----------------------------|---------------------|-------------------------------|
| 22 mm | | | | |
| M206-500-551 | 16 x 20 x 1 | 391 x 492 x 22 | 1,125 | 20 |
| M206-700-551 | 20 x 20 x 1 | 492 x 492 x 22 | 1,410 | |
| M206-319-551 | 12 x 24 x 1 | 289 x 594 x 22 | 1,020 | |
| M206-782-551 | 20 x 24 x 1 | 492 x 594 x 22 | 1,695 | |
| M206-863-551 | 24 x 24 x 1 | 594 x 594 x 22 | 2,040 | |
| M206-600-551 | 16 x 25 x 1 | 391 x 619 x 22 | 1,410 | |
| M206-800-551 | 20 x 25 x 1 | 492 x 619 x 22 | 1,765 | |
| 44 mm | | | | |
| M206-500-552 | 16 x 20 x 2 | 391 x 492 x 44 | 1,860 | 63 |
| M206-700-552 | 20 x 20 x 2 | 492 x 492 x 44 | 2,320 | |
| M206-319-552 | 12 x 24 x 2 | 289 x 594 x 44 | 1,700 | |
| M206-782-552 | 20 x 24 x 2 | 492 x 594 x 44 | 2,800 | |
| M206-863-552 | 24 x 24 x 2 | 594 x 594 x 44 | 3,400 | |
| M206-600-552 | 16 x 25 x 2 | 391 x 619 x 44 | 2,320 | |
| M206-800-552 | 20 x 25 x 2 | 492 x 619 x 44 | 2,900 | |

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

www.aafintl.com



Bringing clean air to life.