

Bag Filters

# DriPak® NXM

**Product Overview**

- AAF design - stable tapered pockets for optimum airflow
- Exceptionally low pressure drop for extremely low energy use
- High efficient synthetic media
- Lightweight



**Specification**

EN779	F7, F9
ASHRAE 52.2	MERV 13, 15
ISO 16890	ePM2.5 55%, ePM1 85%
Filter Depth (mm)	510, 640
Media Type	Synthetic
Frame Material	Galvanised Steel
Special Size Available	Yes
Anitmicrobial Available	No
Single Header	Yes
Recommended Final Resistance	450 Pa
Max Operating Temperature	66°C

BAG FILTERS

**Product Information**

Part Number	Nominal Size Inches (W x H x D)	Actual Size mm (W x H x D)	Number of Pocket	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
<b>F7 / MERV 13 / ePM2.5 55%</b>					
M728-124-200	12 x 24 x 20	289 x 594 x 510	4	1,700	75
M728-136-200	20 x 24 x 20	492 x 594 x 510	6	2,800	
M728-118-200	24 x 24 x 20	594 x 594 x 510	8	3,400	
M728-125-250	12 x 24 x 25	289 x 594 x 640	5	1,700	65
M728-136-250	20 x 24 x 25	492 x 594 x 640	8	2,800	
M728-118-250	24 x 24 x 25	594 x 594 x 640	10	3,400	
<b>F9 / MERV 15 / ePM1 85%</b>					
M720-124-200	12 x 24 x 20	289 x 594 x 510	4	1,700	190
M720-136-200	20 x 24 x 20	492 x 594 x 510	6	2,800	
M720-118-200	24 x 24 x 20	594 x 594 x 510	8	3,400	
M720-125-250	12 x 24 x 25	289 x 594 x 640	5	1,700	120
M720-136-250	20 x 24 x 25	492 x 594 x 640	8	2,800	
M720-118-250	24 x 24 x 25	594 x 594 x 640	10	3,400	

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

[www.aafintl.com](http://www.aafintl.com)



Bringing clean air to life.