

Panel & Pleated Filters

MEGApleat® M8

Product Overview

- Excellent as a pre-filter
- Low operating resistance saves energy
- Highest dust holding capacity
- Strongest construction
- Guaranteed consistent performance
- Patent-pending filter design
- Heavy-duty, galvanised expanded metal support grid



PANEL & PLEATED FILTERS

Specification

EN779	G4
ASHRAE 52.2	MERV 8
ISO 16890	Coarse 60%
Filter Depth (mm)	22, 44, 95
Media Type	Synthetic
Frame Material	Moisture Resistant Beverage Board
Special Size Available	Yes
Antimicrobial Available	No
Recomm. Final Resistance	250 Pa
Max Operating Temperature	93°C
Air Filtration Certificate	UL 900

Product Information

Part Number	Nominal Size Inches (W x H x D)	Actual Size mm (W x H x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
<b>22 mm</b>				
M148-801-500	16 x 20 x 1	391 x 492 x 22	1,860	115
M148-801-700	20 x 20 x 1	492 x 492 x 22	2,320	
M148-801-319	12 x 24 x 1	289 x 594 x 22	1,700	
M148-801-782	20 x 24 x 1	492 x 594 x 22	2,800	
M148-801-863	24 x 24 x 1	594 x 594 x 22	3,400	
<b>44 mm</b>				
M148-802-500	16 x 20 x 2	391 x 492 x 44	1,860	67
M148-802-700	20 x 20 x 2	492 x 492 x 44	2,320	
M148-802-319	12 x 24 x 2	289 x 594 x 44	1,700	
M148-802-782	20 x 24 x 2	492 x 594 x 44	2,800	
M148-802-863	24 x 24 x 2	594 x 594 x 44	3,400	
<b>95 mm</b>				
M148-804-500	16 x 20 x 4	391 x 492 x 95	1,860	47
M148-804-700	20 x 20 x 4	492 x 492 x 95	2,320	
M148-804-319	12 x 24 x 4	289 x 594 x 95	1,700	
M148-804-782	20 x 24 x 4	492 x 594 x 95	2,800	
M148-804-863	24 x 24 x 4	594 x 594 x 95	3,400	

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

www.aafintl.com



Bringing clean air to life.