

Panel & Pleated Filters

PerfectPleat® SC M8

Product Overview

- Low initial resistance
- Mechanical efficiency - does not rely on electret charge technology
- Self-support DuraFlex® media made from virgin fiber; no wire support needed
- Consistent media with controlled fiber size and blend
- Environmentally friendly - no metal, fully incinerable



PANEL & PLEATED FILTERS

Specification

EN779	G4
ASHRAE 52.2	MERV 8
Filter Depth (mm)	44, 95
Media Type	Synthetic
Frame Material	Moisture Resistant Beverage Board
Special Size Available	Yes
Antimicrobial Available	No
Recomm. Final Resistance	250 Pa
Max Operating Temperature	66°C
Air Filtration Certificate	UL 900, ULC-S111

Product Information

Part Number	Nominal Size Inches (W x H x D)	Actual Size mm (W x H x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
44 mm				
T172-102-319	12 x 24 x 2	289 x 594 x 44	1,700	67
T172-102-782	20 x 24 x 2	492 x 594 x 44	2,800	
T172-102-863	24 x 24 x 2	594 x 594 x 44	3,400	
95 mm				
T172-104-319	12 x 24 x 2	289 x 594 x 95	1,700	57
T172-104-782	20 x 24 x 2	492 x 594 x 95	2,800	
T172-104-863	24 x 24 x 2	594 x 594 x 95	3,400	

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

www.aafintl.com



Bringing clean air to life: