

**HT Filters****VariCel® II HT**

HT FILTERS

**Product Overview**

- Minipleat with ribbon separator
- Panel filter with aluminium extrusion frame
- Silicone free construction
- 385°C maximum temperature

**Specification**

EN779	M6 - F8
ASHARE 52.2	MERV 11 - 14
Filter Depth (mm)	55, 78
Media Type	Fibreglass
Frame Material	Aluminium
Separator Style	HT Proseal Tech
Gasket Material	Glass Rope
Special Size Available	Yes
Antimicrobial Available	No
Header Type	None Header
Recommended Final Resistance	450 Pa
Max Operating Temperature	385°C

**Product Information**

Nominal Size Inches (H x W x D)	Actual Size mm (H x W x D)	Rated Airflow (CMH)	Rated Initial Resistance (Pa)
<b>M6 / MERV 11</b>			
12 x 24 x 2	305 x 610 x 55	700	90
24 x 24 x 2	610 x 610 x 55	1,400	
12 x 24 x 3	305 x 610 x 78	700	75
24 x 24 x 3	610 x 610 x 78	1,400	
<b>F7 / MERV 13</b>			
12 x 24 x 2	305 x 610 x 55	700	100
24 x 24 x 2	610 x 610 x 55	1,400	
12 x 24 x 3	305 x 610 x 78	700	80
24 x 24 x 3	610 x 610 x 78	1,400	
<b>F8 / MERV 14</b>			
12 x 24 x 2	305 x 610 x 55	700	110
24 x 24 x 2	610 x 610 x 55	1,400	
12 x 24 x 3	305 x 610 x 78	700	90
24 x 24 x 3	610 x 610 x 78	1,400	

AAF has a policy of continuous product research and improvement and reserves the right to change design and specifications without notice.

[www.aafintl.com](http://www.aafintl.com)

**AAF**  
INTERNATIONAL

Bringing clean air to life.